

Benchmark 

INCUSHAKE *Series*

Shaking Incubators

- + **Exceptional temperature uniformity**
- + **Compact, bench-top design (Mini, just 11" wide)**
- + **Exchange flask clamps in one second with the new **MAGiC CLAMP™** magnetic system**



INCUSHAKE Mini



INCUSHAKE 10L

WITH
MAGiC CLAMP
PATENT PENDING





Incu-Shaker 10L
(H1010)

The new Incu-Shaker™ series of shaking incubators provide digitally regulated temperature with precisely controlled, horizontally circular (orbital) mixing, optimized for the culture of a wide variety of cell types.

The Incu-Shaker Mini is the most compact shaking incubator in its class. Despite the remarkably small footprint, a large 11.5 x 9.5 in. work space accepts several platforms for use with a variety of flasks, tubes and other common vessels.


With similar features to the Incu-Shaker Mini, the Incu-Shaker 10L is equipped with a large 18 x 18 inch platform for high capacity applications. (See Chart for a complete listing of the maximum flask capacity.)

The standard platform (included with both models) features a non-slip, rubber coated surface, ideal for tissue culture flasks, Petri dishes and staining trays. Convenient MAGIC Clamp™ platforms and flask clamps are also available for use with Erlenmeyer flasks and test tube racks. This unique, magnetic attachment method is the easiest way to instantly change between flask clamps of different sizes. Each clamp utilizes a powerful (patent pending) magnetic base to securely attach the clamp to the shaking platform without the use of screws, bolts or tools.

Temperature, shaking speed and run time are displayed on the large LED control panel located on the front of the unit. The integral microprocessor includes a constant monitoring system that verifies and maintains accuracy through the duration of the program. Sophisticated over-temperature and over-speed controls ensure long life, safety and sample integrity.



Incu-Shaker Mini
(H1000-M)



H1010-P-MP



H1010-P-SP



H1000-MR-1550

Technical Data:

Temperature Range:	Ambient +5 to 60°C (Increments of 0.1°C)
Temperature Uniformity:	+/- 0.25 %
Temperature Accuracy:	+/- 0.1 %
Shaking Speed Range:	30 to 300rpm (Increments of 1rpm)
Shaking Orbit:	19mm (3/4")
Platform Dimensions:	
Incu-Shaker Mini	9.5 x 11.5 in. / 23.5 x 29.2 cm
Incu-Shaker 10L	17.8 x 17.8 / 45 x 45 cm
Exterior Dimensions:	
Incu-Shaker Mini	11 x 15.7 x 10.5 in. / 28 x 40 x 27 cm
Incu-Shaker 10L	20 x 26 x 19 in. / 51 x 65 x 47 cm
Weight:	
Incu-Shaker Mini	25 lbs. / 11.5 kg
Incu-Shaker 10L	120 lbs / 55 kg
Electrical:	120 or 230V, 50-60Hz

Maximum capacity of Erlenmeyer flasks

Flask Size:	Incu-Shaker Mini	Incu-Shaker 10L
50ml	20	49
125ml	12	36
250ml	8	25
500ml	5	16
1L	0	9
2L	0	5

Ordering Information

H1000-M*	Incu-Shaker Mini, includes standard rubber mat platform, 115V
H1010*	Incu-Shaker 10L, includes standard rubber mat platform, 115V

*To order an item in 230V, add (-E) to item number.

Optional Platforms and Shelves

H1000-MR	MAGic Clamp universal platform, for Incu-Shaker Mini (9.5x11.5")
H1010-MR	MAGic Clamp universal platform, for Incu-Shaker 10L (18x18")
H1000-P-MP	Microplate platform, 4 position for Incu-Shaker Mini
H1010-P-MP	Microplate platform, 6 position for Incu-Shaker 10L
H1000-P-SP	Spring rack platform, holds uncommon vessels for Incu-Shaker Mini
H1010-P-SP	Spring rack platform, holds uncommon vessels for Incu-Shaker 10L
H1010-SH	Optional Shelf, for Petri Dishes, microplates, trays, etc. (14 x 5.5") for Incu-Shaker 10L (max. 3)

Flask & Tube Rack Accessories for MAGic Clamp Platforms

H1000-MR-50	Flask Clamp, 50ml (H1000-MR: max. 20 / H1010-MR: max. 49)
H1000-MR-125	Flask Clamp, 125ml (H1000-MR: max. 12 / H1010-MR: max. 36)
H1000-MR-250	Flask Clamp, 250ml (H1000-MR: max. 8 / H1010-MR: max. 25)
H1000-MR-500	Flask Clamp, 500ml (H1000-MR: max. 5 / H1010-MR: max. 16)
H1000-MR-1000	Flask Clamp, 1000ml (H1010-MR: max. 9)
H1000-MR-2000	Flask Clamp, 2000ml (H1010-MR: max. 5)
H1000-MR-MP	Microplate Clamp, (H1000-MR: max. 4 / H1010-MR: max. 6)
H1000-MR-1550	Tube Rack, 12x50 & 21x15 ml tubes (H1000-MR: max. 1 / H1010-MR: max. 4)
H1000-MR-T15	Tube Rack, 32x15 tubes (H1000-MR: max. 2 / H1010-MR: max. 8)
H1000-MR-T50	Tube Rack, 15x50 tubes (H1000-MR: max. 2 / H1010-MR: max. 8)
H1000-MR-T600	Bottle Rack, 4x500/600ml conical bottles (H1000-MR: max. 1 / H1010-MR: max. 2)