

Data Sheet

Mixing / Magnetic Stirrers



topolino

Extremely convenient magnetic mini-stirrer for mixing quantities up to 250 ml.

- Durable, brushless motor
- Infinitely variable speed range
- High magnetic adhesion
- Speed range: 300 1800 rpm

Accessories: IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON®

Number of stirring positions 1 Stirring quantity max. per stirring position (H2O) [I] 0.25 Motor rating output [W] 0.8 Speed control stepless Speed range [rpm] 300 - 1800 Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10		
Number of stirring positions 1 Stirring quantity max. per stirring position (H2O) [I] 0.25 Motor rating output [W] 0.8 Speed control stepless Speed range [rpm] 300 - 1800 Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10		
Stirring quantity max. per stirring position (H2O) [I] 0.25 Motor rating output [W] 0.6 Speed control stepless Speed range [rpm] 300 - 1800 Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Technical Data	
Motor rating output [W] 0.8 Speed control stepless Speed range [rpm] 300 - 1800 Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Number of stirring positions	1
Speed control stepless Speed range [rpm] 300 - 1800 Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Stirring quantity max. per stirring position (H2O) [I]	0.25
Speed range [rpm] 300 - 1800 Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Motor rating output [W]	0.8
Stirring bar length max. [mm] 30 Set-up plate material synthetic (PP) Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Speed control	stepless
Set-up plate material synthetic (PP Set-up plate dimensions [mm] Ø 80 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Speed range [rpm]	300 - 1800
Set-up plate dimensions [mm] Ø 86 Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Stirring bar length max. [mm]	30
Dimensions (W x H x D) [mm] 95 x 37 x 115 Weight [kg] 0.32 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Set-up plate material	synthetic (PP)
Weight [kg] 0.33 Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Set-up plate dimensions [mm]	Ø 80
Permissible ambient temperature [°C] 5 - 40 Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Dimensions (W x H x D) [mm]	95 x 37 x 115
Permissible relative humidity [%] 80 Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Weight [kg]	0.32
Protection class according to DIN EN 60529 IP 21 Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Permissible ambient temperature [°C]	5 - 40
Voltage [V] 100 - 240 Frequency [Hz] 50/60 Power input [W] 10	Permissible relative humidity [%]	80
Frequency [Hz] 50/60 Power input [W] 10	Protection class according to DIN EN 60529	IP 21
Power input [W] 10	Voltage [V]	100 - 240
	Frequency [Hz]	50/60
Ident. No. 0003368000	Power input [W]	10
	Ident. No.	0003368000

stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, RSE Stirring bar remover, BC 1000 Beaker cap