Pocomoke City, MD 21851
Batesville, IN 47006
http://www.riccachemical.com
1-888-GO-RICCA
customerservice@riccachemical.com

Product Specification

Bromine Number Titration Solvent, Dichloromethane Formulation

Lot Number: SAMPLE Product Number: 1191

Manufacture Date: N/A Expiration Date: N/A

Arlington, TX 76012

Dichloromethane must be used in place of 1,1,1-Trichloroethane for all operations of this ASTM procedure (i.e., for the dilution of samples and as the titration blank) when this reformulated Titration Solvent is used.

| Name | CAS# | Grade | |
|--------------------|-----------|-----------------|--|
| Acetic Acid | 64-19-7 | ACS | |
| Methylene Chloride | 75-09-2 | ACS | |
| Methyl Alcohol | 67-56-1 | ACS | |
| Sulfuric Acid | 7664-93-9 | ACS | |
| Water | 7732-18-5 | ACS/ASTM/USP/EP | |

| Test | Specification | Result |
|------------|------------------|--------|
| Appearance | Colorless liquid | N/A |

| Specification |
|---------------|
|---------------|

Test Method for Bromine Numbers of Petroleum Distillates and Commercial Aliphatic Olefins by Electrometric Titration ASTM (D 1159)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

| Part Number | Size / Package Type | Shelf Life (Unopened Container) |
|-------------|---------------------------|---------------------------------|
| 1191-32 | 1 L amber glass | 24 months |
| 1191-5PT | 2.5 L safety-coated glass | 24 months |
| 1191-1 | 4 L safety-coated glass | 24 months |

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This Certificate of Analysis is designed to comply with ISO Guide 31 "Reference Materials \cdots Contents of Certificates and Labels."

Version: 1.3 Lot Number: SAMPLE Product Number: 1191 Page 1 of 1