

Product Specification

Sodium Hydroxide, 10.0 Normal

Lot Number: SAMPLE

Product Number: 7470

Manufacture Date: N/A

Expiration Date: N/A

Name	CAS#	Grade
Water	7732-18-5	ACS/ASTM/USP/EP
Sodium Hydroxide	1310-73-2	Reagent

Test	Specification	Result	NIST SRM#
Appearance	Colorless liquid	N/A	
Assay (vs. Sulfuric Acid/Phenolphthalein)	9.95-10.05 N at 20°C	N/A	723
Heavy Metals (as Pb)	max 10 ppm	N/A	
Iron (Fe)	max 5 ppm	N/A	3126

Specification	Reference
Sodium hydroxide Solution (400 g/L)	ASTM (D 3590 A)
Sodium Hydroxide Solution (400 g/L)	ASTM (D 1426 B)
Sodium Hydroxide, 10 N	APHA (4500-NH3 D)
Sodium Hydroxide, 10 N	APHA (4500-CN- L)
Sodium Hydroxide Stock Solution	APHA (4500-NO3- H)
Sodium Hydroxide, 10 N	APHA (7500-Ra D)
ISA Solution (10 M NaOH)	EPA (SW-846) (9213)
Sodium Hydroxide Solution (10 N)	EPA (SW-846) (3510C)
Sodium Hydroxide Solution (10 N)	EPA (SW-846) (3520C)
Sodium Hydroxide (10 N)	EPA (SW-846) (3650B)
Sodium Hydroxide Solution (10 N)	EPA (SW-846) (3535)
Sodium Hydroxide Solution (10 Molar)	EPA (SW-846) (3542)
Sodium Hydroxide, 10 N	EPA (350.3)
Sodium Hydroxide, 10 N	EPA (351.4)
Sodium Hydroxide Stock Solution (10 N)	EPA (353.1)
Sodium Hydroxide, 10 N	EPA (110.1)

Volumetric glassware complies with Class A tolerance requirements of ASTM E 288 and NIST Circular 434; it is calibrated before first use and recalibrated regularly in accordance with ASTM E 542 and NIST Procedure NBSIR 74-461. Balances are calibrated regularly with weights certified traceable to the NIST national mass standard. Thermometers and temperature probes are calibrated before first use and recalibrated regularly with a thermometer traceable to NIST standards. All products are prepared according to master documents that assure manufacture according to validated methods. Batch records document raw material traceability and production and testing history for each lot manufactured.

Part Number	Size / Package Type	Shelf Life (Unopened Container)
7470-2.5	10 L Cubitainer®	24 months
7470-4	120 mL natural poly	24 months
7470-32	1 L natural poly	24 months
7470-5HP	20 L Ropak™	24 months
7470-5	20 L Cubitainer®	24 months
7470-220	220 gal tote	24 months
7470-330	330 gal tote	24 months

7470-1	4 L natural poly	24 months
7470-1CT	4 L Cubitainer®	24 months
7470-16	500 mL natural poly	24 months
7470-50	50 gal drum	24 months
7470-55	55 gal drum	24 months

Recommended Storage: 15°C - 30°C (59°F - 86°F)

This Certificate of Analysis is designed to comply with ISO Guide 31 "Reference Materials -- Contents of Certificates and Labels."